

## Data sheet

<b>Range:</b>	-49.9 to 299.9 °C
<b>Operating Range:</b>	-20 to +50 °C
<b>Resolution:</b>	0.1 °C or 1 °C - user selectable
<b>Accuracy:</b>	±0.3°C (-19.9 to 119.9 °C)±0.4°C (-49.9 to 199.9 °C) otherwise ±1 °C
<b>Battery:</b>	1 x 1.5 volt AAA
<b>Battery Life:</b>	2000 hours (without backlight), 100 hours backlight on time
<b>Sensor Type:</b>	K thermocouple
<b>Display:</b>	14.3mm (horizontal) x 11.85mm (vertical) LCD
<b>Backlight:</b>	Yes
<b>Dimensions:</b>	48.2mm x 156.2mm x 19.3mm
<b>Weight:</b>	115 grams
<b>Case Material:</b>	ABS plastic includes Biomaster product protection
<b>Country of Manufacture:</b>	United Kingdom
<b>Guarantee:</b>	five years
<b>Water/Dust Resistance:</b>	IP67 protection
<b>Measurement Scale:</b>	Celsius/Fahrenheit
<b>Certification:</b>	FREE traceable calibration certificate
<b>Probe Diameter:</b>	ø3.3mm Fast Response
<b>Probe Length:</b>	110mm
<b>Conforms to Standard:</b>	EN 13485
<b>UKCA / CE Status:</b>	CE 1639 Approved

## Specific References

<b>EAN13</b>	5024368187864
--------------	---------------